



FD83075 OLP

## Spring Retractable Fuel Reels

**F7000** - 3/4" I.D.

**FE9000, FD9000** - 3/4", 1" I.D.

**FF9000** - 1/4", 1 1/2" I.D.

**F80000, FD80000** - 3/4", 1" I.D.



Reelcraft's spring retractable fuel delivery reels, equipped with Viton seals, incorporate metal forms to insure the greatest possible strength and are ideal for mobile and permanent-mount applications. These rugged, corrosion-resistant reels are suitable for a wide variety of fuel applications including E85. Series F/FD/FE reels are all supplied with our ball-bearing style swivel.

Model with Hose	Shipping Weight		Pressure	Hose I.D.		Hose O.D.		(M)NPTF Outlet	(F)NPTF Inlet	Hose Length	Model without hose & bumper		Shipping Weight		Pressure	Size Index			
	lbs	kg		in	mm	in	mm	in	in		ft	m	lbs	kg			psi	bar	
<b>Low Pressure Air/Water Reels</b> Maximum Temperature 150° F (65° C) w/hose / 210° F (99° C) w/o hose																			
F7925 OLP*	47	21	*50	3	3/4	19	1.188	30	3/4	3/4	25	8	F7900 OLP		45	20	500	35	pg. 10
F83050 OLP*	89	40	*50	3	3/4	19	1.188	30	3/4	3/4	50	15	F83000 OLP		74	34	500	35	pg. 13
FD83075 OLP*	115	52	*50	3	3/4	19	1.188	30	3/4	3/4	75	23	FD83000 OLP		82	37	500	35	pg. 13
FD84050 OLP*	115	52	*50	3	1	25	1.500	38	1	1	50	15	FD84000 OLP		84	38	500	35	pg. 13
FE9350 OLP*	140	64	*50	3	3/4	19	1.188	30	3/4	3/4	50	15	FE9300 OLP		115	52	500	35	pg. 15
FE9450 OLP*	157	71	*50	3	1	25	1.500	38	1	1	50	15	FE9400 OLP		115	52	500	35	pg. 15
FD9350 OLP*	140	64	*50	3	3/4	19	1.188	30	3/4	3/4	50	15	FD9300 OLP		114	52	500	35	pg. 15
FD9450 OLP*	157	71	*50	3	1	25	1.500	38	1	1	50	15	FD9400 OLP		113	51	500	35	pg. 15
Not available with hose				1	1 1/4	32	1.750	44	1	1 1/4	50	15	FF9500 OLPBW		125	57	600	41	pg. 15
Not available with hose				1	1 1/2	38	2.000	51	1	1 1/2	50	15	FF9600 OLPBW		135	61	600	41	pg. 15

\*Models equipped with fuel grade hose. UL330 and ULC approved hose. 250 PSI minimum burst (17 Bar) For all metric thread connections 1" and under add the suffix number -70 to indicate BSPT threads - example FD80000-OLP70. For all metric threads above 1" add -70 for BSPP threads. FF Models supplied with 1 1/2" inlet. Reel inlet on all models in this chart is NPTF (F) and matches hose I.D. Flow rates of fuel hose are reduced by 30% with addition of internal spring type bend restrictors. For example, flow rate of F7925 OLP with internal bend restrictors is 9.0 GPM at 40 psi; flow without internal bend restrictors is 13.0 GPM at 40 psi.

### Available Options

**Mounting Brackets**  
See page 47



**Inlet Hose Assemblies**  
See page 49



**Replacement Bumpers**  
See page 49



**Replacement Hoses**  
See page 50



## Spring Retractable Grounding Reels

### Series G 3000

Static discharge reels are used to ground equipment operating in hazardous atmospheres. When properly clamped to ground, the static discharge reel dissipates static electrical buildup, reducing the chances of sparking and the potential for explosion.



GA3100 N



G 3050 Y

G 3050

Model	Cable Extended		Y	Clamp Rating	Cable Notes	Shipping Weight	
	ft	m				lbs	kg
G 3050	50	15	N/A	100 AMP	Single 7 x 7 stranded steel*	12	5
G 3050 Y	50	15	2 @ 15' (5)	100 AMP	35' (9.2m) plus dual 15' (4.6m) for Y* Total extension 50' (15m)	12	5
G 3050 N	50	15	N/A	100 AMP	Nylon covered cable**	12	5
GA3100 N	100	30	N/A	100 AMP	Hi-vis orange nylon covered cable**	16	7

\*3/32" OD steel aircraft cable. DC resistance is approximately one ohm per 50 ft. of steel cable. \*\*Nylon covered cable (1/8" O.D.). **Dimensions:** G 3050's = 8.62" x 3.35" x 8.81" (L x W x H); 4 mounting holes (3/8") 7 7/8" x 1 1/2". GA3100 N = 9.25" x 4.31" x 9 3/4" (L x W x H); 4 mounting holes (1/2") 7 7/8" x 1 1/8".

Models listed with an icon can be shipped same day upon request when the order is received by 11:30 AM local time for quantities of 5 or fewer.

Indiana Warehouse

California Warehouse

Indiana & California Warehouses

Canadian Warehouse