

CAPACITY

| | ft / m | | ft / m | | ft / m | |
|--|--------|-----|--------|----|--------|----|
| Hose I.D. | 1/4 | 6 | 3/8 | 10 | 1/2 | 13 |
| Hose O.D. | .530 | 14 | .688 | 18 | .845 | 22 |
| MODEL | LENGTH | | | | | |
| | ft / m | | ft / m | | ft / m | |
| Spring Driven - Pressure 4500 psi / 345 bar (*hose included) | | | | | | |
| PW7600 OHP | — | — | 50 | 15 | — | — |
| PW7650 OHP* | — | — | 50 | 15 | — | — |
| PW81000 OHP | — | — | 100 | 31 | — | — |
| Hand Crank - Pressure 3000 psi / 207 bar; Maximum Temperature | | | | | | |
| H18006 M | 150 | 46 | 100 | 31 | — | — |
| CA38106 M | 200 | 61 | 140 | 43 | 100 | 31 |
| CA38112 M | 425 | 130 | 300 | 91 | 200 | 61 |
| Electric Motor Driven - Pressure 3000 psi / 207 bar; Maximum Temperature | | | | | | |
| EA38106 M12D | 200 | 61 | 140 | 43 | 100 | 31 |
| EA38112 M12D | 425 | 130 | 300 | 91 | 200 | 61 |